

YS6B SERIES
6W



Features


- Energy efficiency level VI
- Class II Power Supply
- 3 Years Warranty
- Universal AC input/Full range
- No load power consumption < 0.1W
- Protections: Short Circuit /Over Load / Over Voltage
- -20~+70℃wide range working temperature

Applications


- Digital Equipment
- Industrial Equipments
- Consumer Electronic Devices
- Telecommunication Devices



Model Description



Dimensions and installation



Standard Cable	1.2m UL2468 (Option: UL2464, UL1185)
5V	20AWG
9 ~ 12V	22AWG
15 ~ 36V	24AWG



Specification


Model	Order P/N	YS6-0501200B-D1J	YS6-0900600B-D1J	YS6-1200500B-D1J	YS6-1500400B-D1J	YS6-2400250B-D1J	YS6-3600160B-D1J	YS6-4800125B-D1J
	Safety Model No.	YS6-0501200B	YS6-0900600B	YS6-1200500B	YS6-1500400B	YS6-2400250B	YS6-3600160B	YS6-4800125B
Output	DC Voltage	5V	9V	12V	15V	24V	36V	48V
	Rated Current	1.2A	0.66A	0.5A	0.4A	0.25A	0.16A	0.125A
	Rated Power	6W	6W	6W	6W	6W	5.76W	6W
	Ripple & Noise(max.)	75mVp-p	90mVp-p	120mVp-p	150mVp-p	240mVp-p	300mVp-p	360mVp-p
	Voltage Tolerance	±5%	±5%	±5%	±5%	±5%	±5%	±5%
	Line Regulation	±3%	±3%	±3%	±3%	±3%	±3%	±3%
	Load Regulation	±5%	±5%	±5%	±5%	±5%	±5%	±5%
	Setup,Rise,Hold up Time	1.0s,30ms,25ms/230VAC(at full load)				2.0s,30ms,12ms/115VAC(at full load)		
Input	Rated Voltage Range	100-240VAC						
	Voltage Range	90-264VAC						
	Frequency Range	50/60Hz						
	AC Current	0.2A/115VAC		0.15A/230VAC				
	Inrush Current	Cold Start 50A/200us at 230VAC 50Hz				Cold Start 30A/200us at 115VAC 50Hz		
	Leakage Current	<0.25mA/230VAC						
	Efficiency	75%	79%	79%	79.5%	80%	80%	80.5%
	No Load Power Consumption	<0.1W						
Protection	Over Load	105~150% Hiccup mode, recovers automatically after fault condition is removed.						
	Short Circuit	Shut down o/p voltage, re-power on to recover.						
	Over Voltage	120~180% Shut down o/p voltage, re-power on to recover.						
Ambient	Working TEMP.	-20 ~ +70 ℃ (Please refer to “Derating Curve”section)						
	Working Humidity	20 ~ 95%RH Non-condensing						
	Storage TEMP. Humidity	-40 ~ +85 ℃ ,10 ~ 95%RH Non-condensing						
	TEMP. Coefficient	±0.03%/(0 ~ 40 ℃)						
	Vibration	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes						
Safety	Safety Standards	BS EN IEC 62368-1						
	Withstand Voltage	I/P-O/P: 3KVAC/1min						
	Isolation Resistance	I/P-O/P:100M Ohms / 500VDC / 25 ℃ / 70% RH						
EMC	EMC Emission	Parameter	Standard		Test Level			
		Conducted	BS EN55032(CISPR32)		CLASS B			
		Radiated	BS EN55032(CISPR32)		CLASS B			
		Harmonic Current	BS EN61000-3-2		CLASS B			
		Voltage flicker	BS EN61000-3-3		CLASS B			
	EMC Immunity	Parameter	Standard		Test Level			
		ESD	BS EN61000-4-2		Level 3, 8KV air, criteria A			
		Radiated Susceptibility	BS EN61000-4-3		Level 3, criteria A			
		EFT/Burest	BS EN61000-4-4		Level 3, criteria A			
		Surge	BS EN61000-4-5		Level 4, 2KV/L-N, criteria A			
		Conducted	BS EN61000-4-6		Level 3, criteria A			
		Magnetic Field	BS EN61000-4-8		Level 4, criteria A			
		Voltage Dips and interruptions	BS EN61000-4-11		> 95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods			
Others	Packing	120g/pcs; 62 x 48 x 38 cm; 100pcs/carton						
	Dimension (LxWxH)	62 x 48 x 38 mm						
	Plug and Cable	See page 3~5; Other type available by customer requested						
	MTBF	245.8Khrs min. MIL-HDBK-217F(25 ℃)						
Note	1. Tolerance: includes set up tolerance, line regulation and load regulation. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3.Line regulation is measured from low line to high line at rated load. 4.Load regulation is measured from 0% to 100% rated load. 5. All parameters NOT specially mentioned are measured at nominal voltage input, rated load and 25 ℃ of ambient temperature. 6. De-rating may be needed under low input voltages. Please refer to “Static Characteristic” sections for details. 7. The power supply is considered as a component that will be operated in combination with final equipment.Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.							

File last modification time: 2025-2-25


YS6B SERIES
6W

Feature Curves

1. Derating Curve



2. Static Characteristics





DC Output Plug (Option)

Standard Model : D1J



Optional DC plug:

Tuning Fork Style			Straight
Type No.	A	B	C
	OD	ID	L
D1I	5.5	2.1	9.5
D1L	5.5	2.5	9.5
D1M	5.5	2.5	11.0

Tuning Fork Style			Right-angled
Type No.	A	B	C
	OD	ID	L
D1IR	5.5	2.1	9.5
D1JR	5.5	2.1	11.0
D1LR	5.5	2.5	9.5
D1MR	5.5	2.5	11.0


YS6B SERIES

6W


DC Output Plug (Option)

Barrel Style				Straight
Type No.	A	B	C	
	OD	ID	L	
D2I	5.5	2.1	9.5	
D2J	5.5	2.1	11.0	
D2L	5.5	2.5	9.5	
D2M	5.5	2.5	11.0	

Barrel Style				Right-angled
Type No.	A	B	C	
	OD	ID	L	
D2IR	5.5	2.1	9.5	
D2JR	5.5	2.1	11.0	
D2LR	5.5	2.5	9.5	
D2MR	5.5	2.5	11.0	

Lock Style				Floating Locking SWITCHCRAFT original or equivalent
Type No.	A	B	C	
	OD	ID	L	
D2S(S761K)	5.53	2.03	12.06	
D2K(761K)	5.53	2.54	12.06	
D2C(S760K)	5.53	2.03	9.52	
D2D(760K)	5.53	2.54	9.52	

Center Pin Style				EIAJ equivalent
Type No.	A	B	C	D
	OD	ID	L	Center Pin
D4A	5.5	3.4	11.0	1.0
D4B	6.5	4.4	11.0	1.4
D4C	7.4	5.1	11.0	0.6

Tuning Fork Style				EIAJ equivalent
Type No.	A	B	C	
	OD	ID	L	
D3A	2.35	0.7	11.0	
D3B	4.0	1.7	11.0	
D3C	4.75	1.7	11.0	


MIN.Din 3Pin with Lock(male)				KYCON KPPX-3P equivalent
Type No.	Pin Assignment			
	PIN No.	Output		
M6B	1	+Vo		
	2	-Vo		
	3	+Vo		


YS6B SERIES

6W


DC Output Plug (Option)

MIN.Din 4Pin with Lock(male)	   KYCON KPPX-4P equivalent	
	Pin Assignment	
Type No.	PIN No.	Output
M7B	1	+Vo
	2	-Vo
	3	-Vo
	4	+Vo

MIN.Din 4Pin with Lock(female)	   KYCON KPJX-CM-4S equivalent	
	Pin Assignment	
Type No.	PIN No.	Output
M7BF	1	+Vo
	2	-Vo
	3	-Vo
	4	+Vo

Barrel Style	  	
	Pin Assignment	
Type No.	PIN No.	Output
M1B	1	-Vo
	2	-Vo
	3	+Vo
	4	-Vo
	5	+Vo

Stripped and tinned leads	  Length of Land L1 by request YJ's standard length, L: 30 mm, L1: 5 mm NOTE: The wire color is for reference only, please refer to the actual product	
	Pin Assignment	
Type No.	PIN No.	Output
by customer	1	+Vo
	2	-Vo

Type-C	  A B C		
			
Type No.	A	B	C
	OD	ID	L
C1	2.4	1.3	8.25