

YS50-Class II SERIES

60W



Features

- Energy efficiency level VI
- Class II Power Supply
- 3 Years Warranty
- Universal AC input/Full range
- No load power consumption < 0.21W
- Protections: Short Circuit /Over Load / Over Voltage
- -30~+70℃ wide range working temperature

Applications

- Office Facilities
- Industrial Equipments
- Consumer Electronic Devices
- Telecommunication Devices



RoHS

CB
SCHEME

Model Description

YS50 - XXXYYYY - □ - D1J

DC Plug Type

D1J: standard model, $\phi 2.1 \times \phi 5.5 \times 11\text{mm}$, C+, tuning fork type

Other options available by customer requested (see Page3-5)


AC Plug Type: C8

Output Current


Output Voltage

Series Name

Dimensions and installation

(Unit: mm , tolerance: $\pm 1\text{mm}$)

Standard Cable	1.2m UL2464 (Option: UL2468, UL1185)
9 ~ 15V	18AWG
24V	20AWG
36 ~ 48V	22AWG



File last modification time: 2025-3-24

Specification


Model	Order P/N	YS50-0905000 -C8-D1J	YS50-1205000 -C8-D1J	YS50-1504000 -C8-D1J	YS50-2402500 -C8-D1J	YS50-3601660 -C8-D1J *	YS50-4801000 -C8-D1J *
	Safety Model No.	YS50-0905000	YS50-1205000	YS50-1504000	YS50-2402500	YS50-3601660	YS50-4801000
Output	DC Voltage	9V	12V	15V	24V	36V	48V
	Rated Current	5A	5A	4A	2.5A	1.66A	1A
	Rated Power	45W	60W	60W	60W	60W	48W
	Ripple & Noise(max.)	100mVp-p	150mVp-p	150mVp-p	200mVp-p	300mVp-p	400mVp-p
	Voltage Tolerance	±5%	±5%	±5%	±5%	±5%	±5%
	Line Regulation	±3%	±3%	±3%	±3%	±3%	±3%
	Load Regulation	±5%	±5%	±5%	±5%	±5%	±5%
	Setup,Rise,Hold up Time	0.8s,30ms,80ms/230VAC(at full load)				2.0s,30ms,15ms/115VAC(at full load)	
Input	Rated Voltage Range	100-240VAC					
	Voltage Range	90-264VAC					
	Frequency Range	50/60Hz					
	AC Current	1.5A/115VAC		0.8A/230VAC			
	Inrush Current	Cold Start 60A/200us at 230VAC 50Hz				Cold Start 40A/200us at 115VAC 50Hz	
	Leakage Current	<0.25mA/230VAC					
	Efficiency	88%	88%	88.5%	88.5%	90%	90.5%
	No Load Power Consumption	<0.21W					
Protection	Over Load	105~150%					
		Hiccup mode, recovers automatically after fault condition is removed.					
	Short Circuit	Shut down o/p voltage, re-power on to recover.					
	Over Voltage	120~180%					
Shut down o/p voltage, re-power on to recover.							
Ambient	Working TEMP.	-30 ~ +70 ℃ (Please refer to “Derating Curve”section)					
	Working Humidity	20 ~ 95%RH Non-condensing					
	Storage TEMP. Humidity	-40 ~ +85 ℃ ,10 ~ 95%RH Non-condensing					
	TEMP. Coefficient	±0.03%/(0 ~ 40 ℃)					
	Vibration	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes					
Safety	Safety Standards	UL62368-1, TUV BS EN/EN62368-1, IEC/EN 61558-1, AS/NZS 62368-1, EAC TP TC 004 approved					
	Withstand Voltage	I/P-O/P: 3KVAC/1min					
	Isolation Resistance	I/P-O/P:100M Ohms / 500VDC / 25 ℃ / 70% RH					
EMC	EMC Emission	Parameter		Standard		Test Level	
		Conducted		EN55032(CISPR32)		CLASS B	
		Radiated		EN55032(CISPR32)		CLASS B	
		Harmonic Current		EN61000-3-2		CLASS B	
		Voltage flicker		EN61000-3-3		CLASS B	
	EMC Immunity	Parameter		Standard		Test Level	
		ESD		EN61000-4-2		Level 3, 8KV air, criteria A	
		Radiated Susceptibility		EN61000-4-3		Level 3, criteria A	
		EFT/Burest		EN61000-4-4		Level 3, criteria A	
		Surge		EN61000-4-5		Level 4, 2KV/L-N, criteria A	
		Conducted		EN61000-4-6		Level 3, criteria A	
		Magnetic Field		EN61000-4-8		Level 4, criteria A	
		Voltage Dips and interruptions		EN61000-4-11		> 95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods	
Others	Packing	310g/pcs; 34 x 31 x 37 cm; 50pcs/carton					
	Dimension (LxWxH)	116.5 x 54.2 x 34.6 mm					
	Plug and Cable	See page 3~5; Other type available by customer requested					
	MTBF	354.9Khrs min. MIL-HDBK-217F(25 ℃)					
Note	1. Tolerance: includes set up tolerance, line regulation and load regulation. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3.Line regulation is measured from low line to high line at rated load. 4.Load regulation is measured from 0% to 100% rated load. 5. All parameters NOT specially mentioned are measured at nominal voltage input, rated load and 25 ℃ of ambient temperature. 6. De-rating may be needed under low input voltages. Please refer to “Static Characteristic” sections for details. 7. The power supply is considered as a component that will be operated in combination with final equipment.Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again. 8. YS50-3601660 does not have Indian BIS IS13252 certification, YS50-4801000 without UL. 9. Safety Model number for EN61558-1 is:YS50N-XXXXYYY.						

File last modification time: 2025-3-24


YS50-Class II SERIES
60W

Feature Curves

1. Derating Curve




2. Static Characteristics







DC Output Plug (Option)

Standard Model : D1J



Optional DC plug:
(Unit: mm , tolerance: ±0.5mm)


Tuning Fork Style			
Type No.	A	B	C
	OD	ID	L
D1I	5.5	2.1	9.5
D1L	5.5	2.5	9.5
D1M	5.5	2.5	11.0

Tuning Fork Style			
Type No.	A	B	C
	OD	ID	L
D1IR	5.5	2.1	9.5
D1JR	5.5	2.1	11.0
D1LR	5.5	2.5	9.5
D1MR	5.5	2.5	11.0


YS50-Class II SERIES


60W


DC Output Plug (Option)


Barrel Style				Straight
Type No.	A	B	C	
	OD	ID	L	
D2I	5.5	2.1	9.5	
D2J	5.5	2.1	11.0	
D2L	5.5	2.5	9.5	
D2M	5.5	2.5	11.0	

Barrel Style				Right-angled
Type No.	A	B	C	
	OD	ID	L	
D2IR	5.5	2.1	9.5	
D2JR	5.5	2.1	11.0	
D2LR	5.5	2.5	9.5	
D2MR	5.5	2.5	11.0	

Lock Style				Floating Locking SWITCHCRAFT original or equivalent
Type No.	A	B	C	
	OD	ID	L	
D2S(S761K)	5.53	2.03	12.06	
D2K(761K)	5.53	2.54	12.06	
D2C(S760K)	5.53	2.03	9.52	
D2D(760K)	5.53	2.54	9.52	

Center Pin Style				EIAJ equivalent
Type No.	A	B	C	D
	OD	ID	L	Center Pin
D4A	5.5	3.4	11.0	1.0
D4B	6.5	4.4	11.0	1.4
D4C	7.4	5.1	11.0	0.6


Tuning Fork Style				EIAJ equivalent
Type No.	A	B	C	
	OD	ID	L	
D3A	2.35	0.7	11.0	
D3B	4.0	1.7	11.0	
D3C	4.75	1.7	11.0	


MIN.Din 3Pin with Lock(male)				KYCON KPPX-3P equivalent
Type No.	Pin Assignment			
	PIN No.	Output		
M6B	1	+Vo		
	2	-Vo		
	3	+Vo		


YS50-Class II SERIES


60W


DC Output Plug (Option)

MIN.Din 4Pin with Lock(male)	   KYCON KPPX-4P equivalent	
	Pin Assignment	
	PIN No.	Output
	1	+Vo
	2	-Vo
	3	-Vo
	4	+Vo

MIN.Din 4Pin with Lock(female)	   KYCON KPJX-CM-4S equivalent	
	Pin Assignment	
	PIN No.	Output
	1	+Vo
	2	-Vo
	3	-Vo
	4	+Vo

Barrel Style	  	
	Pin Assignment	
	PIN No.	Output
	1	-Vo
	2	-Vo
	3	+Vo
	4	-Vo
	5	+Vo

Stripped and tinned leads	  Length of Land L1 by request YJ's standard length, L: 30 mm, L1: 5 mm NOTE: The wire color is for reference only, please refer to the actual product	
	Pin Assignment	
	PIN No.	Output
	1	+Vo
	2	-Vo

Type-C			
Type No.	A	B	C
	OD	ID	L
C1	2.4	1.3	8.25