

# YS80-Class II SERIES

## 90W



### Features

- Energy efficiency level VI
- Class II Power Supply
- 3 Years Warranty
- Universal AC input/Full range
- No load power consumption < 0.21W
- Protections: Short Circuit /Over Load / Over Voltage
- -30~+70℃wide range working temperature

### Applications

- Office Facilities
- Industrial Equipments
- Consumer Electronic Devices
- Telecommunication Devices



RoHS



FC



### Model Description

YS80 - XXXYYYY - [ ] - D1J

DC Plug Type { D1J: standard model,  $\phi 2.1 \times \phi 5.5 \times 11$ mm, C+, tuning fork type  
Other options available by customer requested (see Page3-5)

AC Plug Type: C8


Output Current

Output Voltage




Series Name

### Dimensions and installation

(Unit: mm , tolerance:  $\pm 1$ mm)



| Standard Cable | 1.2m UL2468 (Option: UL2464, UL1185) |
|----------------|--------------------------------------|
| 12 ~ 24V       | 18AWG                                |
| 36V            | 20AWG                                |
| 48V            | 22AWG                                |



C8

## Specification

| Model      | Order P/N                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | YS80-1207500<br>-C6-D1J                                                           | YS80-1506000<br>-C6-D1J | YS80-2403750<br>-C6-D1J                                                      | YS80-3602500<br>-C6-D1J |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------|------------------------------------------------------------------------------|-------------------------|
|            | Safety Model No.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | YS80-1207500                                                                      | YS80-1506000            | YS80-2403750                                                                 | YS80-3602500            |
| Output     | DC Voltage                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 12V                                                                               | 15V                     | 24V                                                                          | 36V                     |
|            | Rated Current                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 7.5A                                                                              | 6A                      | 3.75A                                                                        | 2.5A                    |
|            | Rated Power                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 90W                                                                               | 90W                     | 90W                                                                          | 90W                     |
|            | Ripple & Noise(max.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 100mVp-p                                                                          | 150mVp-p                | 200mVp-p                                                                     | 300mVp-p                |
|            | Voltage Tolerance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | ±5%                                                                               | ±5%                     | ±5%                                                                          | ±5%                     |
|            | Line Regulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | ±3%                                                                               | ±3%                     | ±3%                                                                          | ±3%                     |
|            | Load Regulation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | ±5%                                                                               | ±5%                     | ±5%                                                                          | ±5%                     |
|            | Setup,Rise,Hold up Time                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1.0s,40ms,30ms/230VAC(at full load)                                               |                         | 1.5s,45ms,20ms/115VAC(at full load)                                          |                         |
| Input      | Rated Voltage Range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 100-240VAC                                                                        |                         |                                                                              |                         |
|            | Voltage Range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 90-264VAC                                                                         |                         |                                                                              |                         |
|            | Frequency Range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 50/60Hz                                                                           |                         |                                                                              |                         |
|            | AC Current                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 2.3A/115VAC                                                                       |                         | 1.5A/230VAC                                                                  |                         |
|            | Inrush Current                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Cold Start 60A/200us at 230VAC 50Hz                                               |                         | Cold Start 40A/200us at 115VAC 50Hz                                          |                         |
|            | Leakage Current                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | <0.25mA/230VAC                                                                    |                         |                                                                              |                         |
|            | Efficiency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 89%                                                                               | 89.5%                   | 89%                                                                          | 91.5%                   |
|            | No Load Power Consumption                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <0.21W                                                                            |                         |                                                                              |                         |
| Protection | Over Load                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 105~150%<br>Hiccup mode, recovers automatically after fault condition is removed. |                         |                                                                              |                         |
|            | Short Circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Shut down o/p voltage, re-power on to recover.                                    |                         |                                                                              |                         |
|            | Over Voltage                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 120~180%<br>Shut down o/p voltage, re-power on to recover.                        |                         |                                                                              |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                   |                         |                                                                              |                         |
| Ambient    | Working TEMP.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -30 ~ +70 ℃ (Please refer to “Derating Curve”section)                             |                         |                                                                              |                         |
|            | Working Humidity                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 20 ~ 95%RH Non-condensing                                                         |                         |                                                                              |                         |
|            | Storage TEMP. Humidity                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | -40 ~ +85 ℃ ,10 ~ 95%RH Non-condensing                                            |                         |                                                                              |                         |
|            | TEMP. Coefficient                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | ±0.03%/(0 ~ 40 ℃ )                                                                |                         |                                                                              |                         |
|            | Vibration                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes           |                         |                                                                              |                         |
| Safety     | Safety Standards                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | UL62368-1, IEC61558, KC K60950-1 approved                                         |                         |                                                                              |                         |
|            | Withstand Voltage                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | I/P-O/P: 3KVAC/1min                                                               |                         |                                                                              |                         |
|            | Isolation Resistance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | I/P-O/P:100M Ohms / 500VDC / 25 ℃ / 70% RH                                        |                         |                                                                              |                         |
| EMC        | EMC Emission                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Parameter                                                                         | Standard                | Test Level                                                                   |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Conducted                                                                         | EN55032(CISPR32)        | CLASS B                                                                      |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Radiated                                                                          | EN55032(CISPR32)        | CLASS B                                                                      |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Harmonic Current                                                                  | EN61000-3-2             | CLASS B                                                                      |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Voltage flicker                                                                   | EN61000-3-3             | CLASS B                                                                      |                         |
|            | EMC Immunity                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Parameter                                                                         | Standard                | Test Level                                                                   |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | ESD                                                                               | EN61000-4-2             | Level 3, 8KV air, criteria A                                                 |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Radiated Susceptibility                                                           | EN61000-4-3             | Level 3, criteria A                                                          |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | EFT/Burest                                                                        | EN61000-4-4             | Level 3, criteria A                                                          |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Surge                                                                             | EN61000-4-5             | Level 4, 2KV/L-N, criteria A                                                 |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Conducted                                                                         | EN61000-4-6             | Level 3, criteria A                                                          |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Magnetic Field                                                                    | EN61000-4-8             | Level 4, criteria A                                                          |                         |
|            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Voltage Dips and interruptions                                                    | EN61000-4-11            | > 95% dip 0.5 periods, 30% dip 25 periods,<br>>95% interruptions 250 periods |                         |
| Others     | Packing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 395g/pcs; 34 x 31 x 37 cm; 50pcs/carton                                           |                         |                                                                              |                         |
|            | Dimension (LxWxH)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 116.8 x 34 x 55.5 mm                                                              |                         |                                                                              |                         |
|            | Plug and Cable                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | See page 3~5; Other type available by customer requested                          |                         |                                                                              |                         |
|            | MTBF                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 415.1Khrs min. MIL-HDBK-217F(25 ℃ )                                               |                         |                                                                              |                         |
| Note       | 1. Tolerance: includes set up tolerance, line regulation and load regulation.<br>2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.<br>3.Line regulation is measured from low line to high line at rated load.<br>4.Load regulation is measured from 0% to 100% rated load.<br>5. All parameters NOT specially mentioned are measured at nominal voltage input, rated load and 25 ℃ of ambient temperature.<br>6. De-rating may be needed under low input voltages. Please refer to “Static Characteristic” sections for details.<br>7. The power supply is considered as a component that will be operated in combination with final equipment.Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again. |                                                                                   |                         |                                                                              |                         |

File last modification time: 2025-3-24

YS80-Class II SERIES  
90W

Feature Curves

1. Derating Curve



2. Static Characteristics







DC Output Plug (Option)

Standard Model : D1J



Optional DC plug:  
(Unit: mm , tolerance: ±0.5mm)

| Tuning Fork Style |  |  |  |
|-------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| Type No.          | A                                                                                   | B                                                                                   | C                                                                                   |
|                   | OD                                                                                  | ID                                                                                  | L                                                                                   |
| D1I               | 5.5                                                                                 | 2.1                                                                                 | 9.5                                                                                 |
| D1L               | 5.5                                                                                 | 2.5                                                                                 | 9.5                                                                                 |
| D1M               | 5.5                                                                                 | 2.5                                                                                 | 11.0                                                                                |

| Tuning Fork Style |  |  |  |
|-------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| Type No.          | A                                                                                     | B                                                                                     | C                                                                                     |
|                   | OD                                                                                    | ID                                                                                    | L                                                                                     |
| D1IR              | 5.5                                                                                   | 2.1                                                                                   | 9.5                                                                                   |
| D1JR              | 5.5                                                                                   | 2.1                                                                                   | 11.0                                                                                  |
| D1LR              | 5.5                                                                                   | 2.5                                                                                   | 9.5                                                                                   |
| D1MR              | 5.5                                                                                   | 2.5                                                                                   | 11.0                                                                                  |


# YS80-Class II SERIES

## 90W


### DC Output Plug (Option)

| Barrel Style |  |  |  | Straight |
|--------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|----------|
| Type No.     | A                                                                                 | B                                                                                 | C                                                                                 |          |
|              | OD                                                                                | ID                                                                                | L                                                                                 |          |
| D2I          | 5.5                                                                               | 2.1                                                                               | 9.5                                                                               |          |
| D2J          | 5.5                                                                               | 2.1                                                                               | 11.0                                                                              |          |
| D2L          | 5.5                                                                               | 2.5                                                                               | 9.5                                                                               |          |
| D2M          | 5.5                                                                               | 2.5                                                                               | 11.0                                                                              |          |

| Barrel Style |  |  |  | Right-angled |
|--------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------|
| Type No.     | A                                                                                   | B                                                                                   | C                                                                                   |              |
|              | OD                                                                                  | ID                                                                                  | L                                                                                   |              |
| D2IR         | 5.5                                                                                 | 2.1                                                                                 | 9.5                                                                                 |              |
| D2JR         | 5.5                                                                                 | 2.1                                                                                 | 11.0                                                                                |              |
| D2LR         | 5.5                                                                                 | 2.5                                                                                 | 9.5                                                                                 |              |
| D2MR         | 5.5                                                                                 | 2.5                                                                                 | 11.0                                                                                |              |

| Lock Style |  |  |  | Floating Locking<br>SWITCHCRAFT original or equivalent |
|------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------|
| Type No.   | A                                                                                   | B                                                                                   | C                                                                                   |                                                        |
|            | OD                                                                                  | ID                                                                                  | L                                                                                   |                                                        |
| D2S(S761K) | 5.53                                                                                | 2.03                                                                                | 12.06                                                                               |                                                        |
| D2K(761K)  | 5.53                                                                                | 2.54                                                                                | 12.06                                                                               |                                                        |
| D2C(S760K) | 5.53                                                                                | 2.03                                                                                | 9.52                                                                                |                                                        |
| D2D(760K)  | 5.53                                                                                | 2.54                                                                                | 9.52                                                                                |                                                        |

| Center Pin Style |  |  |  | EIAJ equivalent |
|------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-----------------|
| Type No.         | A                                                                                     | B                                                                                     | C                                                                                     | D               |
|                  | OD                                                                                    | ID                                                                                    | L                                                                                     | Center Pin      |
| D4A              | 5.5                                                                                   | 3.4                                                                                   | 11.0                                                                                  | 1.0             |
| D4B              | 6.5                                                                                   | 4.4                                                                                   | 11.0                                                                                  | 1.4             |
| D4C              | 7.4                                                                                   | 5.1                                                                                   | 11.0                                                                                  | 0.6             |


| Tuning Fork Style |  |  |  | EIAJ equivalent |
|-------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-----------------|
| Type No.          | A                                                                                   | B                                                                                   | C                                                                                   |                 |
|                   | OD                                                                                  | ID                                                                                  | L                                                                                   |                 |
| D3A               | 2.35                                                                                | 0.7                                                                                 | 11.0                                                                                |                 |
| D3B               | 4.0                                                                                 | 1.7                                                                                 | 11.0                                                                                |                 |
| D3C               | 4.75                                                                                | 1.7                                                                                 | 11.0                                                                                |                 |

| MIN.Din 3Pin with Lock(male) |  |  |  | KYCON KPPX-3P equivalent |
|------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------------------|
| Type No.                     | Pin Assignment                                                                        |                                                                                       |                                                                                       |                          |
|                              | PIN No.                                                                               | Output                                                                                |                                                                                       |                          |
| M6B                          | 1                                                                                     | +Vo                                                                                   |                                                                                       |                          |
|                              | 2                                                                                     | -Vo                                                                                   |                                                                                       |                          |
|                              | 3                                                                                     | +Vo                                                                                   |                                                                                       |                          |

# YS80-Class II SERIES


## 90W


### DC Output Plug (Option)

| MIN.Din<br>4Pin with<br>Lock(male) |   <br>KYCON KPPX-4P equivalent |        |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
|                                    |  <br>KYCON KPJX-CM-4S equivalent                                                                            |        |
| Type No.                           | Pin Assignment                                                                                                                                                                                                                                                                    |        |
|                                    | PIN No.                                                                                                                                                                                                                                                                           | Output |
| M7B                                | 1                                                                                                                                                                                                                                                                                 | +Vo    |
|                                    | 2                                                                                                                                                                                                                                                                                 | -Vo    |
|                                    | 3                                                                                                                                                                                                                                                                                 | -Vo    |
|                                    | 4                                                                                                                                                                                                                                                                                 | +Vo    |

| MIN.Din<br>4Pin with<br>Lock(female) |  <br>KYCON KPJX-CM-4S equivalent |        |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
|                                      |  <br>KYCON KPJX-CM-4S equivalent |        |
| Type No.                             | Pin Assignment                                                                                                                                                                                         |        |
|                                      | PIN No.                                                                                                                                                                                                | Output |
| M7BF                                 | 1                                                                                                                                                                                                      | +Vo    |
|                                      | 2                                                                                                                                                                                                      | -Vo    |
|                                      | 3                                                                                                                                                                                                      | -Vo    |
|                                      | 4                                                                                                                                                                                                      | +Vo    |

| Barrel<br>Style |   <br>KYCON KPPX-4P equivalent |        |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| Type No.        | Pin Assignment                                                                                                                                                                                                                                                                          |        |
|                 | PIN No.                                                                                                                                                                                                                                                                                 | Output |
| M1B             | 1                                                                                                                                                                                                                                                                                       | -Vo    |
|                 | 2                                                                                                                                                                                                                                                                                       | -Vo    |
|                 | 3                                                                                                                                                                                                                                                                                       | +Vo    |
|                 | 4                                                                                                                                                                                                                                                                                       | -Vo    |
|                 | 5                                                                                                                                                                                                                                                                                       | +Vo    |

| Stripped<br>and<br>tinned<br>leads |  <br>Length of Land L1 by request<br>YJ's standard length, L: 30 mm, L1: 5 mm<br>NOTE: The wire color is for reference only,<br>please refer to the actual product |        |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| Type No.                           | Pin Assignment                                                                                                                                                                                                                                                                                                                               |        |
|                                    | PIN No.                                                                                                                                                                                                                                                                                                                                      | Output |
| by<br>customer                     | 1                                                                                                                                                                                                                                                                                                                                            | +Vo    |
|                                    | 2                                                                                                                                                                                                                                                                                                                                            | -Vo    |

| Type-C   |  <br>A: 2.4mm, B: 1.3mm, C: 8.25mm |     |      |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|------|
| Type No. | A                                                                                                                                                                                                        | B   | C    |
|          | OD                                                                                                                                                                                                       | ID  | L    |
| C1       | 2.4                                                                                                                                                                                                      | 1.3 | 8.25 |