

YS125-Class II SERIES

150W



Features


- Energy efficiency level VI
- Class II Power Supply
- 3 Years Warranty
- Universal AC input/Full range
- No load power consumption < 0.21W
- Protections: Short Circuit /Over Load / Over Voltage
- -30~+70℃ wide range working temperature

Applications

- Office Facilities
- Industrial Equipments
- Consumer Electronic Devices
- Telecommunication Devices




Model Description



Dimensions and installation

(Unit: mm , tolerance: ±1mm)



Standard Cable	1.2m UL2464 (Option: UL2468, UL1185)
12 ~ 15V	16AWG
24 ~ 36V	18AWG
48V	20AWG

File last modification time: 2025-3-24

Specification


Model	Order P/N	YS125-12012500 -C6-M7B	YS125-15010000 -C6-M7B	YS125-24006250 -C6-M7B	YS125-36004160 -C6-M7B
	Safety Model No.	YS125-12012500	YS125-15010000	YS125-24006250	YS125-36004160
Output	DC Voltage	12V	15V	24V	36V
	Rated Current	12.5A	10A	6.25A	4.16A
	Rated Power	150W	150W	150W	150W
	Ripple & Noise(max.)	100mVp-p	150mVp-p	200mVp-p	300mVp-p
	Voltage Tolerance	±5%	±5%	±5%	±5%
	Line Regulation	±3%	±3%	±3%	±3%
	Load Regulation	±5%	±5%	±5%	±5%
	Setup,Rise,Hold up Time	1.0s,15ms,30ms/230VAC(at full load)		1.0s,15ms,25ms/115VAC(at full load)	
Input	Rated Voltage Range	100-240VAC			
	Voltage Range	90-264VAC			
	Frequency Range	50/60Hz			
	AC Current	2.0A/115VAC		1.1A/230VAC	
	Inrush Current	Cold Start 180A/200us at 230VAC 50Hz		Cold Start 90A/200us at 115VAC 50Hz	
	Leakage Current	<0.25mA/230VAC			
	Efficiency	89%	89.5%	89%	91.5%
	No Load Power Consumption	<0.21W			
Protection	Over Load	105~150% Hiccup mode, recovers automatically after fault condition is removed.			
	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed.			
	Over Voltage	120~180% Shut down o/p voltage, re-power on to recover.			
Ambient	Working TEMP.	-30 ~ +70 ℃ (Please refer to “Derating Curve”section)			
	Working Humidity	20 ~ 95%RH Non-condensing			
	Storage TEMP. Humidity	-40 ~ +85 ℃ ,10 ~ 95%RH Non-condensing			
	TEMP. Coefficient	±0.03%/(0 ~ 40 ℃)			
	Vibration	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes			
Safety	Safety Standards	EN62368-1			
	Withstand Voltage	I/P-O/P: 1.5KVAC/1min			
	Isolation Resistance	I/P-O/P:100M Ohms / 500VDC / 25 ℃ / 70% RH			
EMC	EMC Emission	Parameter	Standard	Test Level	
		Conducted	EN55032(CISPR32)	CLASS B	
		Radiated	EN55032(CISPR32)	CLASS B	
		Harmonic Current	EN61000-3-2	CLASS B	
		Voltage flicker	EN61000-3-3	CLASS B	
	EMC Immunity	Parameter	Standard	Test Level	
		ESD	EN61000-4-2	Level 3, 8KV air, criteria A	
		Radiated Susceptibility	EN61000-4-3	Level 3, criteria A	
		EFT/Burest	EN61000-4-4	Level 3, criteria A	
		Surge	EN61000-4-5	Level 4, 2KV/L-N, criteria A	
		Conducted	EN61000-4-6	Level 3, criteria A	
		Magnetic Field	EN61000-4-8	Level 4, criteria A	
		Voltage Dips and interruptions	EN61000-4-11	> 95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods	
Others	Packing	550g/pcs; 42.5 x 22 x 20 cm; 10pcs/carton			
	Dimension (LxWxH)	172.2 x 70.85 x 43.25 mm			
	Plug and Cable	See page 3~5; Other type available by customer requested			
	MTBF	295.8Khrs min. MIL-HDBK-217F(25 ℃)			
Note	1. Tolerance: includes set up tolerance, line regulation and load regulation. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3.Line regulation is measured from low line to high line at rated load. 4.Load regulation is measured from 0% to 100% rated load. 5. All parameters NOT specially mentioned are measured at nominal voltage input, rated load and 25 ℃ of ambient temperature. 6. De-rating may be needed under low input voltages. Please refer to “Static Characteristic” sections for details. 7. The power supply is considered as a component that will be operated in combination with final equipment.Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.				

File last modification time: 2025-3-24


YS125-Class II SERIES
150W

Feature Curves

1. Derating Curve




2. Static Characteristics





DC Output Plug (Option)

Standard Model : M7B

M7B		Pin Assignment	
	KYCON KPPX-4P equivalent	Pin No.	Output
		1	+Vo
		2	-Vo
		3	-Vo
		4	+Vo

Optional DC plug:
(Unit: mm , tolerance: ±0.5mm)


Tuning Fork Style			Straight
Type No.	A	B	C
	OD	ID	L
D1I	5.5	2.1	9.5
D1J	5.5	2.1	11.0
D1L	5.5	2.5	9.5
D1M	5.5	2.5	11.0

Tuning Fork Style			Right-angled
Type No.	A	B	C
	OD	ID	L
D1IR	5.5	2.1	9.5
D1JR	5.5	2.1	11.0
D1LR	5.5	2.5	9.5
D1MR	5.5	2.5	11.0


YS125-Class II SERIES


150W


DC Output Plug (Option)


Barrel Style				Straight
Type No.	A	B	C	
	OD	ID	L	
D2I	5.5	2.1	9.5	
D2J	5.5	2.1	11.0	
D2L	5.5	2.5	9.5	
D2M	5.5	2.5	11.0	

Barrel Style				Right-angled
Type No.	A	B	C	
	OD	ID	L	
D2IR	5.5	2.1	9.5	
D2JR	5.5	2.1	11.0	
D2LR	5.5	2.5	9.5	
D2MR	5.5	2.5	11.0	

Neutrik XLR NC4FX equivalent			
Type No.	Pin Assignment		
	PIN No.	Output	
MIC4	1	+Vo	
	2	+Vo	
	3	-Vo	
	4	-Vo	

Center Pin Style				EIAJ equivalent
Type No.	A	B	C	D
	OD	ID	L	Center Pin
D4A	5.5	3.4	11.0	1.0
D4B	6.5	4.4	11.0	1.4
D4C	7.4	5.1	11.0	0.6


AMP 1-480702-0 (6.35mm) equivalent			
Type No.	Pin Assignment		
	PIN No.	Output	
M4P	1	+Vo	
	2	+Vo	
	3	-Vo	
	4	-Vo	


MIN.Din 3Pin with Lock(male)				KYCON KPPX-3P equivalent
Type No.	Pin Assignment			
	PIN No.	Output		
M6B	1	+Vo		
	2	-Vo		
	3	+Vo		


YS125-Class II SERIES


150W

DC Output Plug (Option)

MOLEX 39-01-2060 (4.2mm) equivalent   		
Type No.	Pin Assignment	
	PIN No.	Output
M6P	1	+Vo
	2	+Vo
	3	+Vo
	4	-Vo
	5	-Vo
	6	-Vo

MIN.Din 4Pin with Lock(female)    KYCON KPJX-CM-4S equivalent		
Type No.	Pin Assignment	
	PIN No.	Output
M7BF	1	+Vo
	2	-Vo
	3	-Vo
	4	+Vo

Barrel Style   		
Type No.	Pin Assignment	
	PIN No.	Output
M1B	1	-Vo
	2	-Vo
	3	+Vo
	4	-Vo
	5	+Vo

Stripped and tinned leads   Length of Land L1 by request YJ's standard length, L: 30 mm, L1: 5 mm NOTE: The wire color is for reference only, please refer to the actual product		
Type No.	Pin Assignment	
	PIN No.	Output
by customer	1	+Vo
	2	-Vo