

# YS35V-U SERIES

## 36W



### Features

- Energy efficiency level VI
- Class II Power Supply
- 3 Years Warranty
- Universal AC input/Full range
- No load power consumption < 0.1W
- Protections: Short Circuit /Over Load / Over Voltage
- -20~+50°C wide range working temperature


### Applications

- Digital Equipment
- Industrial Equipments
- Consumer Electronic Devices
- Telecommunication Devices







### Model Description

YS35V - XXXYYYY U- **D1J**



### Dimensions and installation

(Unit: mm , tolerance:  $\pm 1$ mm)



Standard Cable	1.2m UL2468 (Option: UL2464, UL1185)
5 ~ 9V	18AWG
12V	20AWG
24 ~ 36V	22AWG
48V	24AWG

# YS35V-U SERIES

## 36W

### Specification


Model	Order P/N	YS35V-0505000U-D1J	YS35V-0904000U-D1J	YS35V-1203000U-D1J	YS35V-2401500U-D1J	YS35V-3601000U-D1J	YS35V-4800750U-D1J
	Safety Model No.	YS35V-0505000	YS35V-0904000	YS35V-1203000	YS35V-2401500	YS35V-3601000	YS35V-4800750
Output	DC Voltage	5V	9V	12V	24V	36V	48V
	Rated Current	5A	4A	3A	1.5A	1A	0.75A
	Rated Power	25W	36W	36W	36W	36W	36W
	Ripple & Noise(max.)	75mVp-p	90mVp-p	120mVp-p	200mVp-p	300mVp-p	400mVp-p
	Voltage Tolerance	±5%	±5%	±5%	±5%	±5%	±5%
	Line Regulation	±3%	±3%	±3%	±3%	±3%	±3%
	Load Regulation	±5%	±5%	±5%	±5%	±5%	±5%
	Setup,Rise,Hold up Time	1.0s,30ms,80ms/230VAC(at full load)			2.0s,30ms,15ms/115VAC(at full load)		
Input	Rated Voltage Range	100-240VAC					
	Voltage Range	90-264VAC					
	Frequency Range	50/60Hz					
	AC Current	0.2A/115VAC		0.21A/230VAC			
	Inrush Current	Cold Start 30A/200us at 230VAC 50Hz			Cold Start 15A/200us at 115VAC 50Hz		
	Leakage Current	<0.25mA/230VAC					
	Efficiency	86.4%	87.5%	87.5%	88%	88.5%	89%
	No Load Power Consumption	<0.1W					
Protection	Over Load	105~150% Hiccup mode, recovers automatically after fault condition is removed.					
	Short Circuit	Recovers automatically after fault condition is removed.					
	Over Voltage	120~180% Shut down o/p voltage, re-power on to recover					
Ambient	Working TEMP.	-20 ~ +50 C (Please refer to "Derating Curve"section)					
	Working Humidity	20 ~ 95%RH Non-condensing					
	Storage TEMP. Humidity	-40 ~ +85 C, 10 ~ 95%RH Non-condensing					
	TEMP. Coefficient	±0.03%/(0 ~ 40 C )					
	Vibration	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes					
Safety	Safety Standards	IEC/UL 62368-1					
	Withstand Voltage	I/P-O/P: 3KVAC/1min					
	Isolation Resistance	I/P-O/P:100M Ohms / 500VDC / 25 C / 70% RH					
EMC	EMC Emission	Parameter	Standard			Test Level	
		Conducted	FCC Part15(CISPR22)			CLASS B	
		Radiated	FCC Part15(CISPR22)			CLASS B	
Others	Packing	180g/pcs; 55 x 26 x 24.5 cm; 50pcs/carton					
	Dimension (LxWxH)	89.3 x 35.6 x 54 mm					
	Plug and Cable	See page 3~5; Other type available by customer requested					
	MTBF	154.6Khrs min. MIL-HDBK-217F(25 C )					
Note	<ol style="list-style-type: none"> <li>Tolerance: includes set up tolerance, line regulation and load regulation.</li> <li>Ripple &amp; noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf &amp; 47uf parallel capacitor.</li> <li>Line regulation is measured from low line to high line at rated load.</li> <li>Load regulation is measured from 0% to 100% rated load.</li> <li>All parameters NOT specially mentioned are measured at nominal voltage input, rated load and 25 C of ambient temperature.</li> <li>De-rating may be needed under low input voltages. Please refer to "Static Characteristic" sections for details.</li> <li>The power supply is considered as a component that will be operated in combination with final equipment.Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.</li> </ol>						

# YS35V-U SERIES


## 36W

### Feature Curves

#### 1. Derating Curve





#### 2. Static Characteristics



### DC Output Plug (Option)

Standard Model : D1J

D1J	Pin Assignment
	

Optional DC plug:

(Unit: mm , tolerance:  $\pm 0.5\text{mm}$ )


Tuning Fork Style	Straight		
	A	B	C
Type No.	OD	ID	L
	D1I	5.5	2.1
D1L	5.5	2.5	9.5
D1M	5.5	2.5	11.0


Tuning Fork Style	Right-angled		
	A	B	C
Type No.	OD	ID	L
	D1IR	5.5	2.1
D1JR	5.5	2.1	11.0
D1LR	5.5	2.5	9.5
D1MR	5.5	2.5	11.0


# YS35V-U SERIES

## 36W


### DC Output Plug (Option)


Barrel Style			
	A	B	C
Type No.	OD	ID	L
D2I	5.5	2.1	9.5
D2J	5.5	2.1	11.0
D2L	5.5	2.5	9.5
D2M	5.5	2.5	11.0

Barrel Style			
	A	B	C
Type No.	OD	ID	L
D2IR	5.5	2.1	9.5
D2JR	5.5	2.1	11.0
D2LR	5.5	2.5	9.5
D2MR	5.5	2.5	11.0

Tuning Fork Style			
	A	B	C
Type No.	OD	ID	L
D3A	2.35	0.7	11.0
D3B	4.0	1.7	11.0
D3C	4.75	1.7	11.0

Center Pin Style				
	A	B	C	D
Type No.	OD	ID	L	Center Pin
D4A	5.5	3.4	11.0	1.0
D4B	6.5	4.4	11.0	1.4
D4C	7.4	5.1	11.0	0.6


Barrel Style		
	Pin Assignment	
Type No.	PIN No.	Output
M1B	1	-Vo
	2	-Vo
	3	+Vo
	4	-Vo
	5	+Vo

MIN.Din 3Pin with Lock(male)		
	Pin Assignment	
Type No.	PIN No.	Output
M6B	1	+Vo
	2	-Vo
	3	+Vo


# YS35V-U SERIES


## 36W

### DC Output Plug (Option)

MIN.Din 4Pin with Lock(male)			
	KYCON KPPX-4P equivalent		
Type No.	Pin Assignment		
	PIN No.	Output	
M7B	1	+Vo	
	2	-Vo	
	3	-Vo	
	4	+Vo	

MIN.Din 4Pin with Lock(female)			
	KYCON KPJX-CM-4S equivalent		
Type No.	Pin Assignment		
	PIN No.	Output	
M7BF	1	+Vo	
	2	-Vo	
	3	-Vo	
	4	+Vo	

Type-C			
			
Type No.	A	B	C
	OD	ID	L
C1	2.4	1.3	8.25

Stripped and tinned leads		
	Length of Land L1 by request YJ's standard length, L: 30 mm, L1: 5 mm NOTE: The wire color is for reference only, please refer to the actual product	
Type No.	Pin Assignment	
	PIN No.	Output
by customer	1	+Vo
	2	-Vo