

YSV40 SERIES

40W



Features

- Energy efficiency level VI
- Class II Power Supply
- 3 Years Warranty
- Universal AC input/Full range
- No load power consumption < 0.21W
- Protections: Short Circuit /Over Load / Over Voltage
- -20~+60℃ wide range working temperature

Applications

- Home Appliances
- Access Control Systems
- Consumer Electronic Devices
- Telecommunication Devices



Model Description

YSV40 - XXXYYYY - [] - D1J

DC Plug Type

D1J: standard model, $\phi 2.1 \times \phi 5.5 \times 11\text{mm}$, C+, tuning fork type
Other options available by customer requested (see Page 3-5)

AC Plug Type

Blank: All universal version with interchangeable plugs
Separate plug available by customer requested (see page 3)


Output Current

Output Voltage

Series Name


Dimensions and installation

(Unit: mm, tolerance: $\pm 1\text{mm}$)



Standard Cable	1.2m UL2468 (Option: UL2464, UL1185)
5 ~ 12V	18AWG
15V	20AWG
24V	22AWG
48V	24AWG

Outside $\ominus$ $\oplus$ Inside



File last modification time: 2025-2-25

Specification


Model	Order P/N	YSV40-0505000-D1J	YSV40-0904440-D1J	YSV40-1203330-D1J	YSV40-1502500-D1J	YSV40-2401660-D1J	YSV40-4800830-D1J
	Safety Model No.	YSV40-0505000	YSV40-0904440	YSV40-1203330	YSV40-1502500	YSV40-2401660	YSV40-4800830
Output	DC Voltage	5V	9V	12V	15V	24V	48V
	Rated Current	5A	4.44A	3.33A	2.5A	1.66A	0.83A
	Rated Power	25W	40W	40W	40W	40W	40W
	Ripple & Noise(max.)	100mVp-p	100mVp-p	120mVp-p	240mVp-p	240mVp-p	400mVp-p
	Voltage Tolerance	±5%	±5%	±5%	±5%	±5%	±5%
	Line Regulation	±3%	±3%	±3%	±3%	±3%	±3%
	Load Regulation	±5%	±5%	±5%	±5%	±5%	±5%
	Setup,Rise,Hold up Time	1.0s,40ms,80ms/230VAC(at full load)			2.0s,40ms,15ms/115VAC(at full load)		
Input	Rated Voltage Range	100-240VAC					
	Voltage Range	90-264VAC					
	Frequency Range	50/60Hz					
	AC Current	1.5A/100VAC		1.0A/240VAC			
	Inrush Current	Cold Start 90A/200us at 240VAC 50Hz			Cold Start 50A/200us at 100VAC 50Hz		
	Leakage Current	<0.5mA/240VAC					
	Efficiency	84.5%	88%	88%	88.5%	89%	89.5%
	No Load Power Consumption	<0.21W					
Protection	Over Load	105~150%					
		Hiccup mode, recovers automatically after fault condition is removed.					
	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed.					
	Over Voltage	120~180%					
Hiccup mode, recovers automatically after fault condition is removed.							
Ambient	Working TEMP.	-20 ~ +60 ℃ (Please refer to “Derating Curve”section)					
	Working Humidity	25 ~ 75%RH Non-condensing					
	Storage TEMP. Humidity	-40 ~ +80 ℃ ,10 ~ 95%RH Non-condensing					
	TEMP. Coefficient	±0.03%/(0 ~ 40 ℃)					
	Vibration	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes					
Safety	Safety Standards	IEC 62368-1, EN 62368-1, AS/NZS 62368-1, UL 62368-1					
	Withstand Voltage	I/P-O/P: 3KVAC/1min					
	Isolation Resistance	I/P-O/P:100M Ohms / 500VDC / 25 ℃ / 70% RH					
EMC	EMC Emission	Parameter	Standard			Test Level	
		Conducted	EN55032(CISPR32), FCC Part 15 Subpart B			CLASS B	
		Radiated	EN55032(CISPR32), FCC Part 15 Subpart B			CLASS B	
		Harmonic Current	EN61000-3-2			CLASS B	
		Voltage flicker	EN61000-3-3			CLASS B	
	EMC Immunity	Parameter	Standard			Test Level	
		ESD	EN61000-4-2			Level 3, 8KV air, criteria A	
		Radiated Susceptibility	EN61000-4-3			Level 3, criteria A	
		EFT/Burest	EN61000-4-4			Level 3, criteria A	
		Surge	EN61000-4-5			Level 4, 2KV/L-N, criteria A	
		Conducted	EN61000-4-6			Level 3, criteria A	
		Magnetic Field	EN61000-4-8			Level 4, criteria A	
		Voltage Dips and interruptions	EN61000-4-11			> 95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods	
Others	Packing	200g/pcs; 34.5 x 32.5 x 39.5 cm; 50pcs/carton					
	Dimension (LxWxH)	89.6 x 41 x 63.9 mm					
	Plug and Cable	See page 3~5; Other type available by customer requested					
	MTBF	50.5Khrs min. MIL-HDBK-217F(25 ℃)					
Note	1. Tolerance: includes set up tolerance, line regulation and load regulation. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3.Line regulation is measured from low line to high line at rated load. 4.Load regulation is measured from 0% to 100% rated load. 5. All parameters NOT specially mentioned are measured at nominal voltage input, rated load and 25 ℃ of ambient temperature. 6. De-rating may be needed under low input voltages. Please refer to “Static Characteristic” sections for details. 7. The power supply is considered as a component that will be operated in combination with final equipment.Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again.						

File last modification time: 2025-2-25


YSV40 SERIES
40W

Feature Curves

1. Derating Curve



2. Static Characteristics



Input Plug Type (Option)

Standard models: All

Interchangeable Type(Unfoldable; AC Pin fixed)				
AC Plug	US	EU	AU	UK
Dimension				

DC Output Plug (Option)



Standard Model : D1J


D1J		Pin Assignment
		
		



YSV40 SERIES
40W



DC Output Plug (Option)


(Unit: mm , tolerance: ±0.5mm)


Tuning Fork Style			
Type No.	A	B	C
	OD	ID	L
D1I	5.5	2.1	9.5
D1L	5.5	2.5	9.5
D1M	5.5	2.5	11.0

Tuning Fork Style			
Type No.	A	B	C
	OD	ID	L
D1IR	5.5	2.1	9.5
D1JR	5.5	2.1	11.0
D1LR	5.5	2.5	9.5
D1MR	5.5	2.5	11.0

Barrel Style			
Type No.	A	B	C
	OD	ID	L
D2I	5.5	2.1	9.5
D2J	5.5	2.1	11.0
D2L	5.5	2.5	9.5
D2M	5.5	2.5	11.0

Barrel Style			
Type No.	A	B	C
	OD	ID	L
D2IR	5.5	2.1	9.5
D2JR	5.5	2.1	11.0
D2LR	5.5	2.5	9.5
D2MR	5.5	2.5	11.0



Barrel Style			
Type No.	Pin Assignment		
	PIN No.	Output	
M1B	1	-Vo	
	2	-Vo	
	3	+Vo	
	4	-Vo	
	5	+Vo	

Center Pin Style				
Type No.	A	B	C	D
	OD	ID	L	Center Pin
D4A	5.5	3.4	11.0	1.0
D4B	6.5	4.4	11.0	1.4
D4C	7.4	5.1	11.0	0.6


YSV40 SERIES


40W


DC Output Plug (Option)


Tuning Fork Style			
		EIAJ equivalent	
Type No.	A	B	C
	OD	ID	L
D3A	2.35	0.7	11.0
D3B	4.0	1.7	11.0
D3C	4.75	1.7	11.0

MIN.Din 3Pin with Lock(male)			
		KYCON KPPX-3P equivalent	
Type No.	Pin Assignment		
	PIN No.	Output	
M6B	1	+Vo	
	2	-Vo	
	3	+Vo	

MIN.Din 4Pin with Lock(male)			
		KYCON KPPX-4P equivalent	
Type No.	Pin Assignment		
	PIN No.	Output	
M7B	1	+Vo	
	2	-Vo	
	3	-Vo	
	4	+Vo	

MIN.Din 4Pin with Lock(female)			
		KYCON KPJX-CM-4S equivalent	
Type No.	Pin Assignment		
	PIN No.	Output	
M7BF	1	+Vo	
	2	-Vo	
	3	-Vo	
	4	+Vo	

Type-C			
Type No.	A	B	C
	OD	ID	L
C1	2.4	1.3	8.25

Stripped and tinned leads			
		Length of Land L1 by request YJ's standard length, L: 30 mm, L1: 5 mm NOTE: The wire color is for reference only, please refer to the actual product	
Type No.	Pin Assignment		
	PIN No.	Output	
by customer	1	+Vo	
	2	-Vo	