

YMC10 SERIES

10W




YMC10 is a 10W miniature (40*25.4*21mm) AC-DC module-type power supply, ready to be soldered onto the PCB boards of various kinds of electronic instruments or industrial automation equipments. This product allows the universal input voltage range of 85~305VAC.



Features

- Universal AC Input/ Full Range
- No load power consumption<0.12W
- Wide operating temperature range -40~85℃
- High efficiency up to 84%
- 4x2.54cm compact size
- Protections: Short circuit/Over load/Over voltage
- Operating attitude up to 5000 meters
- Three years warranty

Model Description



Model Information

Part number	DC Voltage	Rated Current(max.)	Rated Power	Efficiency	Max.Capacitive Load	Ripple & Noise
YMC10-3.3□	3.3V	2.6A	8.58W	74%	6600uF	100mVp-p
YMC10-5□	5V	2A	10W	79%	5000uF	100mVp-p
YMC10-9□	9V	1.1A	9.9W	81%	3600uF	100mVp-p
YMC10-12□	12V	0.83A	9.96W	83.5%	2000uF	100mVp-p
YMC10-15□	15V	0.66A	9.9W	83%	820uF	100mVp-p
YMC10-24□	24V	0.41A	9.84W	84%	470uF	100mVp-p

Specification

Model	Safety Model No.	YMC10-XX□			
Output	Voltage Tolerance	±2.0%			
	Line Regulation	±0.5%			
	Load Regulation	±1.0%			
	Setup,Rise,Hold up Time	1.0s,30ms,40ms/230VAC(at full load)		1.5s,30ms,8ms/115VAC(at full load)	
Input	Rated Voltage Range	100-277VAC			
	Voltage Range	85-305VAC/100-430VDC			
	Frequency Range	47-63Hz			
	AC Current	0.23A/115VAC	0.15A/230VAC		
	Inrush Current	Cold Start 80A/400us at 230VAC 50Hz		Cold Start 25A/600us at 115VAC 50Hz	
	Leakage Current	<0.1mA/277VAC			
Protection	Over Load	>110%			
		Shut down o/p voltage, recovers automatically after fault condition is removed.			
	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed.			
	Over Voltage	3.3V: 3.8~9VDC 5V:5.5~9VDC 9V: 10~16VDC 12V:13~15VDC 15V: 17~24VDC 24V: 26~34VDC			
Output voltage clamp or Hiccup mode.					
Ambient	Working TEMP.	-40 ~ +85 ℃ (Refer to"Derating Curve".)			
	Working Humidity	20 ~ 95%RH Non-condensing			
	Storage TEMP. Humidity	-40 ~ +85 ℃,10 ~ 95%RH Non-condensing			
	TEMP. Coefficient	±0.02%/(0 ~ 40 ℃)			
	Vibration	PCB Mounting: 10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes Terminal Blocks: 10 ~ 500Hz, 5G 10min./1cycle, period for 60min. each along X, Y, Z axes			
	Soldering Temperature	Wave soldering:260 ℃,10s(max.); Manual soldering:370 ℃,5s(max.)			
	Over Voltage Category	OVC II; According to EN61558-1; altitude up to 4000 meters			
	Safety Protection	Class II			
Safety	Safety Standards	UL62368-1, EN60335-1 approved , design to meet :BS EN62368-1, EN61558-1			
	Withstand Voltage	I/P-O/P: 4KVAC/1min			
	Isolation Resistance	I/P-O/P:100M Ohms / 500VDC / 25 ℃ / 70% RH			
EMC	EMC Emission	Parameter	Standard	Test Level	
		Conducted	EN55014-1	CLASS B	
		Radiated	EN55014-1	CLASS B	
		Harmonic Current	EN61000-3-2	CLASS A	
		Voltage flicker	EN61000-3-3	
	EMC Immunity	BS EN/EN55035, BS EN/EN61000-6-2			
		Parameter	Standard	Test Level	
		ESD	EN61000-4-2	Level 3, 8KV air, Level 2, 4KV contact, criteria B	
		RF field susceptibility	EN61000-4-3	Level 3, 10V/m criteria A	
		EFT/Burest	EN61000-4-4	Level 3, ±2KV criteria B	
		Surge	EN61000-4-5	Level 3, 1KV/L-L criteria B	
		Conducted	EN61000-4-6	Level 3, 10Vr.m.s criteria A	
Voltage Dips and interruptions		EN61000-4-11	> 95% dip 0.5 periods, 30% dip 25 periods, >95% interruptions 250 periods		
Others	Weight	PCB Mounting: 34g/pcs; Terminal Blocks: 54g/pcs;			
	Packing	PCB Mounting: 42.5 x 34.5 x 16cm 200pcs/Carton; Terminal Blocks: 57 x 27 x 19cm 100pcs/Carton			
	Dimension (LxWxH)	PCB Mounting: 40 × 25.4 x 21 mm; Terminal Blocks: 75.8 × 31.3 x 29.7 mm			
	Housing material	Plastic / UL94-V0			
	MTBF	300Khrs min. MIL-HDBK-217F(25 ℃)			
Note	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25 ℃ of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1μF & 47μF parallel capacitor. 3. The ambient temperature derating of 3.5 ℃ /1000m with fanless models and of 5 ℃ /1000m with fan models for operating altitude higher than 2000m (6500ft). 4. The power supply is considered as an independent unit ,but the final equipment still need to re-confirm that the whole system complies with the EMC directives.For guidance on how to perform these EMC tests,please refer to "EMI testing of component power supplies". (as available on https://yingjiao.com/wp-content/uploads/2025/06/EMI_Testing_of_Component_Power_Supplies_Yingjiao.pdf) 5. If the product is not operated within the required load range the product performance cannot be guaranteed to comply with all parameters in the datasheet. 6.When the output terminal of the product needs to be connected to PE through a Y capacitor, or close to the metal frame, please refer to the Fig. 3 for recommended circuit. 7.Unless otherwise specified, EMC performance indicators are tested according to typical application circuits (Fig. 1).				


File last modification time: 2025-7-18

YMC10 SERIES


10W

Engineering Data


Derating Curve



Static Characteristics




Derating Curve



Note: 1. With an AC input between 85-115VAC and a DC input between 100-165VDC, the output power must be derated as per temperature derating curves.
2. This product is suitable for applications using natural air cooling; for applications in closed environment please consult YINGJIAO.

Dimensions and installation (YMC10-XX)

(Unit: mm , tolerance: $\pm 0.5\text{mm}$)




File last modification time: 2025-7-17

YMC10 SERIES

10W

Dimensions and installation (YMC10-XXT)

(Unit: mm , tolerance: $\pm 0.5\text{mm}$)



Design Reference

1. Typical application




Fig.1: Typical circuit diagram

MODEL	FUSE	R1	C1	C2	TVS
YMC10-3.3□	2A/300V, Slow fuse, must be connected	6.8Ω /3W(Wire wound resistor, must be connected)	1uF/50V	220uF/16V	SMBJ7.0A
YMC10-5 □				220uF/16V	SMBJ7.0A
YMC10-9 □				100uF/25V	SMBJ12A
YMC10-12□				100uF/25V	SMBJ20A
YMC10-15□				100uF/25V	SMBJ20A
YMC10-24 □				100uF/35V	SMBJ30A

Output Filter Components:

We recommend using an electrolytic capacitor with high frequency, and low ESR rating for C2 (refer to manufacture's datasheet). Choose a Capacitor voltage rating with at least 20% margin. C1 is a ceramic capacitor used for filtering high-frequency noise and TVS is a recommended suppressor diode to protect the application in case of a converter failure.

YMC10 SERIES

10W

Design Reference

2.EMC Solution - Recommended circuit




Figure 2:EMC application circuit with higher requirements

Component Type	Recommended Value
MOV	14D561K

3.EMC Solution - Recommended circuit




Figure 3 : category I device recommendation circuit

(Recommended when the output end of the product needs to be connected to PE or connected to PE through a Y capacitor)

Component Type	Recommended Value
FUSE	2A/300V Slow fuse, must be connected
MOV	S14K350
CX	334K/305VAC
R1	12Ω/5W(Winding resistor ,must be connected)
L1	1.2mH/0.3A
CY1/CY2	2.2nF/400VAC
GDT	300V/1KA
LCM	20mH
Note:Rx1/Rx2/Rx3/Rx4/Rx5/Rx6 is the bleed resistance of CX, the recommended resistance value is 1.5MΩ/150VDC	